

XT PRO 56 FORESTRY

OVERCENTER AERIAL DEVICE



SPECS

EQUIPMENT:

WORKING HEIGHT: 61'

BOTTOM PLATFORM HEIGHT: 60'

OVERCENTER SIDE REACH: 45.6'

NON-OVERCENTER SIDE REACH: 41.5'

LOWER BOOM ARTICULATION: 0° TO 125°

UPPER BOOM ARTICULATION: 0° TO 250°

SIDE MOUNTED 24" X 24" X 40" ONE PERSON PLATFORM PLATFORM CAPACITY OF UP TO 400 LBS. (181 KG) CONTROL-PLUS "3-D" SINGLE STICK AT

PLATFORM CONTINUOUS UNRESTRICTED WORM GEAR ROTATION CATEGORY "C" RATING PER ANSI A92.2

FIBERGLASS BOOMS

RECTANGULAR, BI-AXIAL EPOXY RESIN, FILAMENT WOUND INDIVIDUAL LEVER LOWER CONTROLS

MECHANICAL PLATFORM LEVELING

FULL PRESSURE, OPEN-CENTER HYDRAULIC SYSTEM

50 GALLON HYDRAULIC OIL RESERVOIR

PADDED BOOM RESTS WITH UPPER BOOM TIE DOWN BOOM / OUTRIGGER INTERLOCK

MOVING OUTRIGGER ALARM, TRUCK LEVEL INDICATORS 10 YEAR MAINTENANCE FREE LEVELING CHAIN

DUAL HYDRAULIC TOOL OUTLET AT BOOM TIP

MANUAL PLATFORM TILT

STANDARD CONFIGURATION:

11' CHIP BOX AND HOIST ASSEMBLY WITH HOLDING VALVE 48" (4) DOOR THRU BOX

SPRING LOADED CAB GUARD W/ STEPS AND GRAB HANDLES FACTORY DASH MOUNTED PTO SWITCH

(2) WHEEL CHOCKS WITH UNDERBODY STORAGE

(2) OUTRIGGER PADS WITH UNDERBODY STORAGE

ICC REAR BUMPER WITH PH30 PINTLE HOOK

ELECTRONIC TRAILER BRAKE CONTROLLER

(6) PRONG TRAILER SOCKET

33 GALLON HYDRAULIC RESERVOIR

CHASSIS SPECS:

FREIGHTLINER BUSINESS CLASS M2 106, PAINTED WHITE CUMMINS (6.7L) ISB DIESEL, 220 HP

SCR TECHNOLOGY WITH 5 GALLON DEF TANK

50 GALLON ALUMINUM FUEL TANK

121" CAB TO AXLE

ALLISON AUTOMATIC OR 6 SPEED MANUAL TRANSMISSION AIR BRAKES OR HYDRAULIC BRAKES

10,000 LB SET BACK FRONT AXLE

19,000 LB REAR AXLE

FACTORY DE-RATED TO 26,000 LB GVWR (UNDER CDL) 11R22.5G TIRES FRONT (2) AND REAR (4)

50-STATE EMISSIONS COMPLIANT, CA CLEAN IDLE ENGINE BLOCK HEATER

AIR CONDITIONING

DUST/BUG SCREEN MOUNTED BEHIND GRILL

WEATHER BAND AM/FM RADIO

MUD FLAPS







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.