



BROOKS BROTHERS 3RT 212-12KE

THREE REEL MATERIAL TRAILER



SPECS

CAPACITY:

25,900# GVWR-CALCULATED AT 15% WEIGHT TRANSFER TO TOW VEHICLES 20,00# LOAD CAPACITY

DIMENSIONS:

OVERALL LENGTH: 26' A-FRAME: 5' CARGO BED: 21' L X 72" W X 15" H OVERALL WIDTH: 101"

REEL CAPACITY:

(3) THREE X 84" D X 60" W X 3" CENTER HOLE - 8,600 LB. PER REEL CAPACITY

AXLES:

TANDEM 12,000# HEAVY DUTY DEXTER SPRING AXLES ELECTRIC BRAKES ON ALL WHEELS (4) FOUR 235/75R17.5 LR-H TIRES (1) PAIR MUD FLAPS

REEL RACKS:

(3) THREE - FIXED WITH HEAVY DUTY BRONZE BEARINGS, RETAINER CAP, MOUNTS FOR RETRIEVER, PULL PIN & SPRING CAP (3) THREE - 2 7/8" REEL BARS WITH CROSSARM AND (1) ONE LOCKING COLLAR (3)

TENSIONING BRAKE ASSEMBLIES:

(3) - 16" X 3/4" C-46400 ANNEALED NAVAL BRASS BRAKE DISC. HUB, SHAFT AND DISC MACHINED AS ONE UNIT M100 SERIES HAYES BRAKE CALIPER, 10,000 LBS. OF CLAMPING FORCE EASY REPLACEMENT

TONGUE, HITCH & JACK:

5" X 3" TUBULAR STEEL A-FRAME 6-POSITION ADJUSTABLE HITCH PLATE (14" THROUGH 27") 2 1/2" LUNETTE EYE 42K CAPACITY 3/8" X 36" L GALVANIZED SAFETY CHAINS WITH SAFETY HOOKS 12,000 LB. DROPLEG JACK WEATHER PROOF HOLDER FOR OPERATORS MANUAL

MAIN FRAME:

5" X 3" TUBULAR STEEL MAIN FRAME 5" X 3" TUBULAR STEEL CROSSMEMBERS AT FRONT OF CARGO BED 6" X 3" TUBULAR STEEL CROSSMEMBERS AT REAR OF CARGO BED

CARGO BED:

1-1/2" THICK SOLID OAK FLOOR 3" C-CHANNEL & 3" ANGLE CROSSMEMBERS ON 24" CENTERS SIDES - 12 GAUGE STEEL WITH 3" X 3" TUBULAR STEEL TOP RAIL & 5" X 3" LOWER RAIL

CATWALK:

1/8" STEEL DIAMOND TREAD, MOUNTED ON 4" X 2" TUBULAR PERIMETER FRAME FULL LENGTH OF CARGO BED, FORE AND AFT OF FENDERS

FENDERS:

FABRICATED 1/8" STEEL DIAMOND TREAD PLATE FENDERS INTEGRATED CONSTRUCTION WITH CATWALKS

TOOLBOX:

TOOLBOX DIMENSIONS: 14"H X 13"D X 78" CONTOURED TO A FRAME FABRICATED 1/8" SMOOTH STEEL INTERLARDERD CONSTRUCTION LIFT-UP LID WITH SECURITY HASP FOR PADLOCK 12 VOLT

WIRING SYSTEM:

ICC & DOT APPROVED LED LIGHTS SEALED BEAM RUBBER MOUNTED LED STOP, TURN, TAIL & MARKER LIGHTS S.O. CABLE WIRING LOOM, CLAMPED ON 16" CENTERS WITH RUBBER LINED CLAMPS

WIRING LOOM TERMINATED IN JUNCTION BOXES CONNECTIONS SOLDERED & SEALED WITH HEAT SHRINK TUBING 32" PIGTAIL W/ELECTRICAL PLUG, TERMINATED AT JUNCTION BOX BREAKAWAY KIT WITH

SEALED LEAD ACID BATTERY & TRICKLE CHARGER

FINISH:

3 STEP TRIPLE HOT DIPPED GALVANIZED FINISH
2" RED/WHITE REFLECTIVE TAPE



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

