



Load King Stinger 60-110 60Ton Boom New Peterbilt 567

CRANE SPECIFICATIONS

Engine

X15 485V 485Hp
3 Paccar Batteries
18.7 CFM Air Compressor
Intebrake

Transmission

Eaton RTO14908LL 10-Speed

Front Axle

Paccar Steer Axle
20,000 LB, 4" Drop
Tires: 425/65R22.5
Aluminum Wheels

Front Suspension

Taper Leaf Springs
Shocks 20,000 LB

Rear Axle

Dana Spicer T69-170
69,000 Lb Tri-Drive
DIFF Lock Tri-Drive Axles
Ratio 4.10
Tires: 11R22.5
Aluminum Wheels

Rear Suspension

Air Trac Tri-Drive 66,000 LBS
60" Axle Spacing

Fuel Tanks

90 Gallon Aluminum Fuel Tank-LH
Small DEF Tank

Pusher Axle

8,000Lbs Hendrickson
SC8 Self-Steering Pusher
52" Pusher Axle Spacing
Tires: 215/75R17.5
Aluminum Wheels

Cab Features

Aluminum Cab 121" BBC Metton Hood
Cab Air Suspension
Outside Sunvisor - Stainless Steel
Peterbilt Keyless Entry
Peterbilt ST Passenger Seat
Peterbilt ST Driver Seat
Drivers Armrests - LH & RH
Air Ride Driver
Non-Adjustable Passenger Seat
High Back Driver
High Back Passenger
Adjustable Steering Column
Tilt/Telescope
Platinum Interior - Sterling Gray
Day Cab Rear Window
One-Piece Curved Windshield
Power Door Locks
Power Window Lifts
Air Horn Mounted Under Cab
(5) Marker Lights, Aero Led

Load King 60-110 60 Ton Boom

60 Tons Capacity Rating
Mainframe Consists Of All-Steel Formed Construction
X Pattern Hydraulic Swing Out And Telescopic 3 Position
4 Outrigger Beam System
Outrigger Control Station In The Crane Cab
Continuous Rotation (No Swing Stop) Foot Peddle Swing Brake And
360 Degree Swing Lock
Hydraulic Oil Cooler
Premium Contoured Flexible Fenders
Aluminum Diamond Plate Decking
Access Ladders And Steps
Recessed locking storage box in decking
110' Four Section, Full Power,
Mechanically Synchronized Boom
Rated Capacity Limiter System With Digital Read Out Display With
Integrated Work Area Definition Program
Hydraulic Counterweight Removal System With
12,000 Lbs Removeable Counterweight Package
33'-57' (2 Piece) Offsetting Jib
Operators Cab Hydraulically Tilting Fully Adjustable From 0 To 18
Degrees With 6-Way Adjustable Heated Seat
Joystick Controls In Armrests Are Adjustable Fore And AFT, Pivot Up
90° With Shutoff Controls
360-Degree House Lock
Single Main Planetary 2 Speed Hoist
533 FPM (163m/min) Maximum Line Speed
15,639 Lb. (7093 Kg) Maximum Line Pull
Grooved Drum, Tapered Flanges, And Spring Loaded Cable Roller
Tensioner For Improved Spooling
Auxiliary Winch Package With Single Sheave Extension
500' x 5/8" Resistant Cable (both Winches)
12 Ton Load Ball With Hook
3-Sheave (30 Ton) Load Block
Air Shift PTO
(2) Remote Outrigger Control Stations Located Each Side Of Unit

855-399-5991 -- www.loadkingmfg.com

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.
Pictures are representative and may not be identical.

• • PRICE: \$619,900
• • FET Not Applicable
• • Ex Works: Kansas City, MO

QUOTE NUMBER: HC8.10-D_19

EXPIRATION DATE: 6-30-19