

## HOGG & DAVIS OLT38B OVERHEAD LINE TENSIONER



## **SPECS**

TENSIONING DEVICE:

MULTI GROOVE BULLWHEELS

RATED AT: 3000 LBS

JACKSTANDS: MANUAL

UNIT LENGTH: 20' 8", WIDTH: 96"

TANDEM LEAF SPRING AXLES

**ELECTRIC BRAKES** 

LED LIGHT PACKAGE

14,000 LBS GAWR

235/85/16 14 PLY TIRES

**BULLWHEEL SPECIFICATIONS:** 

DIAMETER (WITH LINING): 38"

LINING: (3) URETHANE DIAMETER MOLDED

**GROOVE DIAMETER: 1.5"** 

BRAKING: (2) 1-3/8" THICK DISCS

BRAKE SPECIFICATIONS:

BRAKE MATERIAL: STAINLESS STEEL

DIAMETER: 24"

BRAKING MECHANISM: HYDRAULIC

ACTUATOR: SINGLE SCREW ROTARY ADJUSTMENT

REEL CARRIER SPECIFICATIONS:

REEL CAPACITY: 8,000 LBS.

MAXIMUM REEL WIDTH: 56"

MAXIMUM REEL DIAMETER: 90"

ANTI-OVERSPIN BRAKE: 16" BRONZE

OPTIONAL EQUIPMENT:

MANUAL RETRIEVER FOR REEL

HYDRAULIC REEL RETRIEVER

HYDRAULIC REEL RETRIEVER (TOOL CIRCUIT)

ABS AIR BRAKES

HYDRAULIC OUTRIGGERS (2) REAR

HYDRAULIC TONGUE JACK (1) FRONT

HYDRAULIC OUTRIGGERS COMPLETE (3)

SPARE TIRE & WHEEL

13HP POWER PACK

OPERATOR STATION SEAT







888-925-0858 www.customtruck.com



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.