



# SPECS

GENERAL DESCRIPTION:	50,000 LB. CAPACITY TAG-ALONG TRAILER WITH BEAVERTAIL & RAMPS.
LOAD CAPACITY:	50,000 LBS. AT 55 M.P.H. (G.V.W.R. 59,850 LBS.)
OVERALL LENGTH:	35'-0"
DECK LENGTH:	29'-0" (24'-0" FLAT DECK + 5'-0" BEAVERTAIL)
DECK WIDTH:	8'-6"
DECK HEIGHT:	36" UNLOADED
FRAME CONSTRUCTION:	PIERCED MAINBEAM CONSTRUCTION WITH ONE PIECE INTERLOCKING CROSSMEMBERS. MAINBEAMS: W14" X 26 LBS. PER FT., GRADE 50 HI-TENSILE. CROSSMEMBERS: 6" I-BEAM X 3.7 LBS PER FT., GRADE 50 HI-TENSILE ON 22" CENTERS. 3/16" STEEL FABRICATED KNEE BRACING ON CROSSMEMBERS. SIDERAILS: C8" X 11.5 LBS. PER FT. GRADE 50 HI-TENSILE. 8" CHANNEL, FULL WIDTH OF TRAILER.
HEADBOARD:	2" NOMINAL OAK SECURED TO CROSS-
DECKING:	MEMBERS WITH 5/16" TORQUE SCREWS.
STANDARD PAINT:	SUSPENSION: BLACK ACRYLIC ENAMEL. HUTCH 9700 MULTI-POINT SPRING WITH RADIUS ROD AXLE TRACKING ADJUSTMENT, 66,000 LB. CAPACITY.
AXLES:	(3) DEXTER 22,500 LB. CAPACITY WITH OIL BATH HUBS.
BRAKES:	12-1/4" X 7-1/2" AIR WITH "WABCO" ANTI-LOCK BRAKING SYSTEM AND SPRING PARKING BRAKES.
WHEELS:	8 HOLE, HUB PILOTED STEEL DISC.
TIRES:	(12) 215/75R17.5, (H)
RAMPS:	60" X 22" WOOD-FILLED WITH SPRING ASSIST.
JACK:	25,000 LB. 2 SPEED, SIDE CRANK.
HITCH:	4 POSITION CAST STEEL PINTLE EYE, 1-5/8" STOCK, 3" I.D.
TIE DOWNS:	(8) HEAVY DUTY D-RINGS, 4 PER SIDE.
LIGHTS:	12 VOLT DOT & ICC APPROVED. ALL LIGHTS ARE LED TYPE AND FLUSH MOUNTED IN RUBBER GROMMETS. WIRING IS RUN IN FLEXIBLE NEOPRENE JACKET AND MODULAR IN DESIGN. 7 WAY PLUG.



833-955-7732  
[www.loadkingmfg.com](http://www.loadkingmfg.com)



\*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.