



SPECS

REEL CAPACITY (3): 9,000 LB. CAPACITY, 60" WIDE, 72" TALL, 3" ARBOR SAFELOCK
PINLESS ARBOR BAR LOCKS - NO TOOLS OR PIN REQUIRED
16" STOCKBRIDGE DUAL BRONZE VENTILATED TRU-STOP TENSION BRAKE - 4,200 FT/LBS.
10" BRAKE PADS ON MANUAL CALIPERS, LARGE HAND WHEEL CONTROL
PINTLE HITCH, TANDEM AXLE, THREE REEL TRAILER WITH REEL BRAKES
(2) 15,000 LB. DEXTER AXLES, 8 HOLE PILOT RIMS, OIL BATH HUBS
(4) 285/70R 19.5 TIRES
ELECTRIC BRAKES W/ BREAK AWAY
REINFORCED HD SPRING SUSPENSION
1/4" THICK WALL HEAVY DUTY TUBE STEEL FRAME CONSTRUCTION
ADJUSTABLE (6 POSITION) 15 TON PINTLE HITCH
12,000 LB. MANUAL FRONT TONGUE JACK - (2) REAR MANUAL 12,000 LB. STABILIZER JACKS
RUBBER WHEEL CHALKS, FENDER MOUNTED WHEEL CHALK HOLDERS
DOT / ICC APPROVED LED LIGHTS & REFLECTIVE TAPE
3 STEP HOT DOP GALVANIZING - (10 YEAR STRUCTURAL WARRANTY)

DIMENSIONS:
24' 6" LONG
100.5" WIDE
76" TALL
5,550 LBS. WEIGHT



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

