





# SPECS

## SPECIFICATIONS

MAXIMUM CONTINUOUS TENSION 10,000 LBS. @ 4 MPH

BULLWHEEL DIAMETER 72 INCHES

GROOVE DIAMETER 2.125 INCHES

NUMBER OF GROOVES 5 PER BULLWHEEL

## DIMENSIONS (APPROX)

LENGTH 211 INCHES

WIDTH 89 INCHES

HEIGHT 134 INCHES

WEIGHT 7,000 LBS.

## STANDARD EQUIPMENT

PRECISE HYDRAULIC CONTROL WITH ANTI-SURGE ACCUMULATOR

TILTED BULLWHEELS TO REDUCE CABLE TWIST

44" BRONZE DISC BRAKES

CENTRAL ELEVATED OPERATORS PANEL WITH TENSION CHART

3 ROLLER TAIL FAIRLEAD

TANDEM AXLE TRAILER WITH ELECTRIC BRAKES

FRONT AND REAR DROP-LEG JACKS

TIE DOWN LUGS



888-925-0858

[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

