



SPECS

20" HYDRAULIC TENSION BRAKE - GALVANIZED

GVWR: 20,000 LBS.

TANDEM AXLE - TWO 10,000 LB. DEXTER AXLES, ELECTRIC BRAKES

OIL BATH HUBS, 8 BOLT WHEELS, 215/75R17.5 TIRES

SPRING SUSPENSION

ADJUSTABLE PINTLE HITCH

MANUAL FRONT JACK

(2) MANUAL REAR JACKS

(2) WHEEL CHALK HOLDERS/FENDERS

GROUNDING LUG

"D" RING TIE DOWNS

20 IN. DUAL BRONZE VENTILATED REEL BRACE DISCS

HYDRAULIC CALIPERS W/ REMOTE TONGUE HAND PUMP AND GAUGE

3 IN. ARBOR WITH LIFT AND LOCK COLLAR

PIN-LESS TRU LOCK ARBOR BAR LOCKS

REEL CAPACITY:

60 IN. WIDE

104 IN. TALL

16,000 LB.

DIMENSIONS:

8 FT. WIDE

80 IN. TALL

16 FT. 6 IN. LONG

3,600 LBS.



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

