



SHERMAN + REILLY PT-3000 PULLER-TENSIONER



SPECS

PULLING CAPACITY: 3,000 LB. (RATED AT THE TOP OF DRUM)
TENSIONING CAPACITY: 2,000 LB.
AVERAGE LINE SPEED: PULLING: 4 MPH
MAXIMUM CONDUCTOR REEL SIZE: 66 IN. O.D. X 38 IN. W
MAXIMUM REEL WEIGHT: 6,000 LB., WITH CONDUCTOR
SPINDLE DIAMETER: 2-5/8 IN.
DRIVE SYSTEM: HYDRAULIC, DIRECT DRIVE
ENGINE: TIER 4 DIESEL, 45 HP, WATER COOLED
CENTRALIZED ENGINE CONTROLS: CANBUS OPERATING SYSTEM
HYDRAULIC FLUID: ISO GRADE 32
HYDRAULIC RESERVOIR: 25 GAL.
FAIL-SAFE BRAKE: SPRING-APPLIED, HYDRAULIC PRESSURE RELEASED
FUEL CAPACITY: 18 GAL.
OPERATOR ENCLOSURE: OPEN/HALF ENCLOSED CAB
FRAME CONSTRUCTION: STEEL TUBING, CONTINUOUS WELD
LENGTH, OVERALL, NOMINAL: 16 FT., 9 IN.
WIDTH, OVERALL, NOMINAL: 8 FT., 5 IN.
HEIGHT, OVERALL, NOMINAL: 9 FT., 5 IN.
NET WEIGHT, NO OPTIONS, NOMINAL: 3,995 LB.
GVWR: 10,000 LB.
SUSPENSION: LEAF SPRING
WHEEL CONFIGURATION & TIRES: DUAL, 235/85 R16
AXLE CONFIGURATION: SINGLE
BRAKES, TRAILER: ELECTRIC, WITH BREAK-AWAY SWITCH
FRONT/NOSE JACKS: HYDRAULIC
REAR JACKS: 2 HYDRAULIC
TOWING ATTACHMENT: 3 IN. ADJUSTABLE PINTLE EYE
SAFETY CHAINS: 2 EACH, WITH HOOK
ELECTRICAL SYSTEM: 12 VDC
BATTERY: 12 V, LED, U.S. DOT-APPROVED
GROUNDING: FOUR 3/4 IN. DIAMETER COPPER-CLAD STEEL LOOPS
TIE DOWNS: TWO 5/8 IN. DIAMETER STEEL D-RINGS
TIE OFF POINT: TIE OFF POINT AT REAR BUMPER, 3,000 LB. AT 45°
FIRE EXTINGUISHER: ABC
PAINT: S+R WHITE
PAYOUT BRAKE: HYDRAULIC WITH ELECTRIC CONTROLS
LEVELWIND: OVERHEAD / UNDERGROUND HYDRAULIC



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

