



GALBREATH U4/U5-DPHK-176 ROLL-OFF HOOK HOIST

FOR USE WITH CONTAINER SIZES 16-20'



SPECS

RECOMMENDED CONTAINER SIZE: 16' TO 20'
RATED HOIST CAPACITY: 40K LBS. @ 54" / 50K LBS. @ 61 3/4"
MAX. HOOK HEIGHT (LOAD/UNLOADING): 128 3/8" OR 132 5/8"
MAX. HOOK HEIGHT (DUMPING): 220 5/8" OR 224 3/4"
BACK OF CAB TO HOIST: 3"
DUMP ANGLE: 58°
(CT) CAB TO TRUNNION: 176"
AFTER FRAME: 14 1/2" TO 25" MAX
HOIST LENGTH: 213"
HOOK HEIGHT: 54" OR 61 3/4"
FRAME HEIGHT: 43 5/8" OR LESS
LIFT CYLINDERS - (2) DUAL ACTING: 7" X 3 1/2" X 81"
JIB CYLINDER - (1) DUAL ACTING: 4" X 2 1/2" X 48"
REAR STABILIZER: OPTIONAL
APPROXIMATE WEIGHT W/ STANDARD FEATURES: 7,234 LBS.



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

