

IMT 1610 K3 CRANE

AVAILABLE ON A VARIETY OF CHASSIS BRANDS & MODELS



SPECS

EQUIPMENT:

ARTICULATED FIGURE FOUR MATERIAL HANDLING CRANE

RCL SAFETY SYSTEM

WIRELESS SCANRECO RADIO REMOTE CONTROL

PROPORTIONAL SINGLE CIRCUIT DAN FOSS CONTROL VALVE FOR HIGH SPEED AND INFINITE

CONTROL SINGLE SIDE (BACK UP) OPERATOR CONTROL

POWER LINK ARM SYSTEM WITH 15 DEGREE OVER BEND BETWEEN

MAIN BOOM AND OUTER BOOM 400° ROTATION

DOUBLE-ACTING CYLINDERS WITH PILOT OPERATED LOAD HOLDING VALVES

HIGH PRESSURE FILTER

CRANE IS PAINTED IMT WHITE

BOOM EXTENSIONS AND CYLINDERS ARE PAINTED BLACK

BOOM CONFIGURATION: 3 HYDRAULIC EXTENSIONS TO HORIZONTAL REACH 34' 1"

MAX LIFT AT MAX REACH: 2,822 LB

POWER LINK: SINGLE LINK BETWEEN MAST AND INNER BOOM FOR VERTICAL LIFTING

STABILIZERS: HYDRAULIC EXTENDABLE TO 18' 4"

STABILIZER LEGS: FIXED VERTICAL 2' 6" - 4' 2"

180 DEGREE SWING UP W/FLASHING LIGHT STRIP

CRANE MOUNTED 23.5 GAL HYDRAULIC TANK

CRANE MOUNTED OIL COOLER

LOAD KING BODY SPECIFICATIONS:

16' X 96" STRUCTURELINE PLATFORM

3/16" TREADPLATE FLOOR

4" STRUCTURAL CHANNEL CROSSMEMBERS ON 12" CENTERS 6" STRUCTURAL CHANNEL SIDE AND END RAILS

8" STRUCTURAL CHANNEL LONGSILLS

SLIDING WINCH TRACK FULL LENGTH ON CURB SIDE

48" X 96" HD BULKHEAD W/EXPANDED METAL WINDOW PAINT BLACK







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.