



TEREX COMMANDER 4042

MOUNTED ON IHI-55 W/LOAD KING TILT TOP TRAILER



SPECS

GENERAL SPECIFICATIONS:

TEREX C4042 DIGGER DERRICK

UPPER CONTROLS – 24" X 24" X 42" PLATFORM WITH INSULATED LINER

TRANSFERABLE POLE CLAWS

15,000 LB BOOM WINCH TIP

11,250 LB CAPACITY AT 10' RADIUS

COMMAND POST

RADIAL OUTRIGGER MOUNTED ON

BACK OF TRACK MACHINE

12,000 LB TWO SPEED DIGGER WITH 18" ROCK RIPPER AUGER

20,000LB. FRONT HYDRAULIC WINCH

KATO IC55

KUBOTA V3800 / 105 HP @ 2400 RPM

TIER 4 FINAL

6.2 MPH (LOW) /7.5 MPH (HIGH)

HST TRANSMISSION SYSTEM

19.5" GROUND CLEARANCE /24" TRACK WIDTH

ROPS CANOPY CAB/ WITH HEAT

4042 TRACK DIGGER

O LENGTH – 21'8"

LENGTH – 19'5"

WIDTH – 8'2"

HEIGHT – 9'7"

WEIGHT – 26,840 LBS (CLEAN)

TRACK DIGGER & TRAILER

TRAVEL HEIGHT – 12'10"

APPROX. COMBINED WEIGHT – 38,940 LBS



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

