



SPECS

C4047 DIGGER DERRICK

UPPER CONTROLS - 24" X 24" X 42" PLATFORM WITH INSULATED LINER

TRANSFERABLE POLE CLAWS

15,000 LB BOOM WINCH TIP

9,500 LB CAPACITY AT 10' RADIUS

COMMAND POST

2 SETS - RADIAL OUTRIGGERS MOUNTED ON BACK OF TRACK MACHINE

12,000 LB TWO SPEED DIGGER

WITH 18" ROCK RIPPER AUGER

TERRAMAC RT6

CUMMINS B4.5 PERFORMANCE SERIES

TIER 4 FINAL/EU STAGE V 155 HP

3.9 MPH 1ST GEAR /

6.7 MPH 2ND GEAR

HST TRANSMISSION

21" GROUND CLEARANCE /

27.5" TRACK WIDTH

ENCLOSED SINGLE CAB WITH AC/HEAT

LENGTH: 19'3"

OVERALL LENGTH: 24'6"

WIDTH: 8'3"

HEIGHT: 10'3"

WEIGHT: 29,600 LBS





888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.