



PALFINGER T29L HOOKLIFT

WITH 29,000 lb. CAPACITY



SPECS

LIFT / DUMPCAPACITY (LB.): 29000
CA RANGE (IN.): 150-160"
OPTIMUM CA (IN.): 160
MIN. GVWR (LB.): 33000
HOOKLIFT LENGTH: 193
CLEAR FRAME RAIL (IN.): 198
BODY LENGTH RANGE (FT.): 4.27-5.79 M
OPTIMUM BODY LENGTHS (FT.): 4.8-5.49 M
JIB HEIGHT (IN.): 54"
JIB ACTION: TELESCOPIC
MAX. DUMP ANGLE: 50 DEGREES
PIVOT: DUAL
OF LIFT / DUMP CYLINDERS: 2/2
OPERATING PRESSURE (PSI): 3625
PUMP TYPE: PISTON/DIRECT MOUNT
FITTING HOSES: JIC/SAE
SHIPPING WEIGHT (LB.): 3370
PAINT: PRIMER
CONSTRUCTION: A514 (T-1)



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

