

RT5500 NAVIGATOR ALL-TERRAIN, TRUCK-MOUNTED FORKLIFT

Navigator Standard Specifications

- 5500 LBS @ 24" load center
- Double stage mast, 144" lift height
- 104.5" Overall height
- 75" Mounted overhang
- 100" Machine width
- 5800 LBS Dry weight
- 8° Mast tilt
- 5" Side shift
- 60" Frame opening
- 30" Mast travel
- 31x15.5x15 Tires (3)
- Hydrostatic drive
- 60 HP Kohler diesel Tier four engine
- 8 MPH Max travel speed
- Back up alarm
- 48" Lumber Forks
- Tire sealant
- Parking Brake
- Strobe light
- Load backrest

Navigator Included Options

- 144" Mast lift height
- Nav-reach = single side unload
- Block heater
- Remote Load unload

Navigator Features

- Center positioned suspension seat
- Gauges located in front of operator
- Mast constructed of 6.25" hardened steel mast channel
- Wheel motor hubs gusseted for strength
- Integrated counter weighting increasing performance & strength
- Simplified Steering mechanism
- One piece frame design
- Adjustable guide blocks for carriage alignment
- Made in the USA









888-684-8146 www.customtruck.com
ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING
SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

BASE PRICE:

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions. Please contact our sale representatives for exact specifications and current pricing. Pictures are representative and may not reflect the actual unit.