



SPECS

SHEAVE HEIGHT: 80'
MAXIMUM CAPACITY: 40,290 POUNDS
FOUR STAGE HYDRAULICALLY EXTENDED STEEL BOOMS
TRANSFERRABLE POLE CLAWS
15,000 LB TURRET MOUNTED WINCH
COMMAND POST CONTROL STATION
RADIAL OUTRIGGERS MOUNTED ON TRACK MACHINE
14,000 LB TWO-SPEED DIGGER WITH 24", 30", & 36" ROCK RIPPER AUGERS AVAILABLE
SPRING LOADED HYDRAULIC HOSE REEL
30,000 LB HYDRAULIC WINCH MOUNTED ON THE FRONT OF THE TRACK MACHINE
RUBBER TRACKS

MOROOKA MST 3500VDL
CATERPILLAR C7.1 / 275 HP
TIER 4 EMISSION
0 - 7.5MPH (TRAVEL SPEED)
HST TRANSMISSION SYSTEM WITH
HST+ EMERGENCY BRAKE
20" GROUND CLEARANCE / 33" TRACK WIDTH
RUBBER TRACKS
ENCLOSED SINGLE CAB WITH AC/HEAT
WEIGHT: 58,500 LB | LENGTH: 17'10"
OAL: 33' | HEIGHT: 11'8"

833 - CT - SPECS
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

