

TEREX TM125

125' TRACK BUCKET



SPECS

GENERAL SPECIFICATIONS

125 FT MATERIAL HANDLER

NON-COMPENSATED BOOM / CONTINUOUS ROTATION

2-MAN END MOUNT ROTATING BUCKET WITH 800 LB CAPACITY

TOP MOUNTED HYDRAULIC JIB AND WINCH WITH 1,500 LB CAPACITY

TWO SETS OF OUT AND DOWN OUTRIGGERS

30,000 LB HYDRAULIC WINCH MOUNTED ON THE FRONT OF TRACK MACHINE

MOROOKA MST3500VDL PLUS

CATERPILLAR C7.1 / 270 HP

TIER 4 FINAL

0 - 7.5 MPH (UNLOADED)

HST TRANSMISSION SYSTEM WITH HST + EMERGENCY BRAKE

20" GROUND CLEARANCE / 33" TRACK WIDTH

ENCLOSED SINGLE CAB WITH AC/HEAT

WEIGHT: 70,000 LB. LENGTH: 31'10" | OAL: 41'6" OAW: 9'10" HEIGHT: 11'10"





833 - CT - SPECS www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.