

HOGG & DAVIS ODP60-XP

6,000 LB. SINGLE DRUM PULLER



SPECS

2020 HOGG & DAVIS ODP60-CUSTOM TRUCK XP (EXTRA PERFORMANCE) MODEL

THIS NEW CTOS ODP60 MODEL OFFERS A 30% FASTER PULLING SPEED WITH 6,000 LBS. OF PULLING FORCE. DISENGAGING THE DRIVE SYSTEM ALLOWS FOR FREE WHEEL PAYOUT OF THE PULLING ROPE WITH AN INTEGRATED HYDRAULICALLY CONTROLLED OVERSPIN BRAKE. THE OPERATOR CONTROLLED POST STYLE LEVELWIND ALLOWS FOR EVEN WINDING OF ROPE. ALL UNIT FUNCTIONS ARE CENTRALLY LOCATED AT THE OPERATORS STATION. ENGINE GAUGES INCLUDING TACHOMETER, OIL PRESSURE, TEMP, FUEL, AND VOLTAGE ARE ALL IN VIEW. PUILLING IS CONTROLLED WITH AN ELECTRIC OVER HYDRAULIC FRICTION JOYSTICK ALLOWING FOR INFINITE CONTROL OF LINE SPEED AND PRESETTABLE LINE PULL.

PERFORMANCE:

CONTINUOUS LINEPULL RATING: 6,000 LBS @ 6MPH - 30% FASTER
INFINITELY VARIABLE SPEED FROM 0.0 - 6.88 MPH
1.6 MPH @ CORE - 6.88 MPH MAX TOP OF DRUM - 30% FASTER

TRAILER DATA:

TANDEM 8,000 LB LEAF-SPRUNG AXLES 17,600 LB GVWR
ELECTRIC TRAILER BRAKES
(3) DROP-LEG MANUAL LEVELING JACKS
(4) R17.5 - 16 PLY RATED TIRES
FULL COVERAGE FENDERS WITH MUDFLAPS
D.O.T. TRAILER LIGHTING W/ 7-WIRE CONNECTOR

DRIVE SYSTEM:

NEW 118 HP YANMAR TF4 DIESEL ENGINE
CLOSED LOOP HYDROSTATIC HYDRAULIC DRIVE
SPRING APPLIED, HYDRAULIC RELEASE DRIVE TRAIN BRAKE
MECHANICAL CLUTCH DRUM ENGAGEMENT
STANDARD: FREEWHEEL DISCONNECT
16" DIA. VENTILATED OVERSPIN BRAKE

GENERAL FEATURES:

19 GALLON FUEL CAPACITY
29.5 GALLON HYDRAULIC OIL CAPACITY
HYDRAULIC BOOM LEVELWIND
LOCKABLE STEEL BATTERY BOX

DRUM CAPACITY:

RATED DIAMETER: 58"
WIDTH: 44"
RATED ROPE CAPACITY: 15,160 FEET (3/4" DIA.)

UNIT DIMENSIONS:

LENGTH: 17'6"
WIDTH: 8'6"
HEIGHT (SHIELD UP): 9'4-1 /4"
HEIGHT (SHIELD DOWN): 8'1-3/4"
WEIGHT (CURB): 11,000 LBS







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.