



**POWERTRAXX PT15**

**WITH TEREX GENERAL 65**



# SPECS

## POWERTRAXX PT15 WITH TEREX GENERAL 65

90 DEGREE OF BOOM TRAVEL (+80 TO -10)  
DUAL LIFT CYLINDERS  
SELF-ALIGNING SWIVEL BALL BUSHINGS  
RECTANGULAR, BI-AXEL EXPOXY RISEN, FILAMENT WOUND FIBERGLASS BOOMS BOX  
FRABICATED STEEL LOWER BOOM AND INTERMEDIATE  
HYDRALIC BOOM EXTENTION INTERMEDIATE AND UPPER  
FULL PRESSURE HYDRAULICS CONTROLS  
FULL PRESSURE, OPEN-CENTRE HYDRAULIC SYSTEM  
70 GALLON HYDRAULIC OIL RESERVIOR  
CUSTOM MADE LOAD ZONE CHART  
CONTINUOUS UNRESTRICTED ROTATION  
15,000 LB. PLANETARY TURNTABLE WINCH  
MEETS OR EXCEEDS ANSI A10.31  
PLANETARY PARKING BREAK ROTATION  
RIUGHT-HAND COMMAND POST CONTROLS  
ENGINE STOP/START AT LOWER CONTROLS  
BOOM ANGLE INDAICATOR  
OUTTRIGGER INTERLOCK  
MOVING OUTRIGGER ALARM  
TRUCK LEVEL INDICATOR

### POWERTRAXX PT15

VERSITILE, HIGH PAYLOAD, D DENT, TRACK MACHINE  
CUMMINS 6.7L TIER 4 ENGINE  
LEADING D DENT CARRIER ON THE MARKET

WIDTH = 10'6  
HEIGHT = 12'6  
WEIGHT = 60,000 LBS



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

