



# SPECS

## EQUIPMENT SPECIFICATIONS:

VERSALIFT VST-40-1

WITH A WORKING HEIGHT OF 45' AND HORIZONTAL REACH OF 30'

SIX GPM OPEN CENTER HYD SYSTEM W/ A 3000 PSI OPERATING PRESSURE

SIDE MOUNTED TELESCOPIC UPPER BOOM

FIBERGLASS INNER BOOM

FIBERGLASS LOWER BOOM

BOOM INSERT

NON-LUBE BEARINGS

OUTRIGGER BOOM INTERLOCK SYSTEM

17 GAL RESERVOIR

INDIVIDUAL FULL PRESSURE CONTROLS AT THE TURRET ACTUATE WITH A SELECTOR VALVE TO OVERRIDE UPPER CONTROLS

12V DC BACKUP PUMP

AUTO THROTTLE CONTROL

SAFETY HARNESS AND LANYARD



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

