

LK-122-PT POLE TRAILER

WITH 12,500 LB. PAYLOAD



SPECS

CAPACITY:

23,000LB. GVWR-CALCULATED AT

15% WEIGHT TRANSFER TO TOW VEHICLE 19,000# LOAD CAPACITY

DIMENSIONS:

LENGTH ADJUSTMENTS: 24'/31'/38'

CARGO BED: 12'L X 64"W X 15'H

OVERALL WIDTH: 86"

BOLSTER HEIGHT: 45"

FRONT BOLSTER:

45" TUBULAR BOLSTER

64" TUBULAR BOLSTER

60" WIDE W/ LEVER LOCK STANCHIONS

89" WIDE W/ LEVER LOCK STANCHIONS"

CENTER/REAR BOLSTERS

64" WIDE W/ POLE STOPS

89" WIDE REMOVABLE W/ STANCHIONS

TONGUE & HITCH: 8" X 4" EXTENDABLE TONGUE W/ WEAR PADS"

HITCHPLATE: 6-POSITION ADJUSTABLE WITH 2 1/2" LUNETTE EYE

JACK: 3" LUNETTE EYE

TOOL BOX: 14" TALL X 24" DEEP X 64" WIDE

REEL STANDS:

2,000 LB. CAPACITY - MAX REEL 72" X 48"

3,500 LB. CAPACITY - MAX REEL 72"" X 54"

REEL BAR: 3 7/8" OD - INCLUDED W/ REEL STANDS

RECEIVER POCKETS : ADDITIONAL TO ACCOMMODATE 2 OR 3 REELS







833 - CT - SPECS wwww.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.