





<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.





# **SPECIFICATIONS**

## **FRAME**

- 35 TON CAPACITY (70,000LB)
- 50,000LB IN 10FT
- 20,800LB WEIGHT EST
- 16" PIN SETTING
- 48" KP HEIGHT
- 86" SWING CLEARANCE
- 38" DECK HEIGHT
- CHAIN SLOTS IN OUTER BEAMS, CENTER ON 18" CENTERS
- TAIL LIFTING CAPACITY: 24,000LB

## **RUNNING GEAR**

- (2) 22,500LB CAPACITY AXLES
- TIRE INFLATION PSI PREPPED
- CENTRALIZED GREASE SYSTEM
- 12.25 X 7.5 BRAKES
- 235/75R 17.5 CONTINENTAL TIRES
- STEEL RIMS INSIDE, POLISHED ALUM OUTSIDE
- MANUAL AIR RIDE HEIGHT CONTROL

#### **SYSTEMS**

- HYDRAULIC QUICK COUPLERS (FRONT)
- 2500PSI, 20GPM
- 20,000LB WINCH W/ CABLE TENSIONER
- 3 SPOOL CONTROL VALVE W/ REMOTE CONTROL
- 7-WAY MOLDED ELECTRICAL HARNESS
- LED LIGHTS, EXTRA SIDE MARKERS
- WORK LIGHTS AT WINCH LOCATION

#### **FINISHINGS**

- LOAD KING BLACK POLY PAINT
- 1-3/8" APITONG DECKING
- FULL DECAL PACKAGE







<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.