

## **TEREX TL100**

TRANSMISSION AERIAL DEVICE



\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



## **TEREX TL100**

TRANSMISSION AERIAL DEVICE

## TL100:

BOTTOM OF PLATFORM: 95.0 FT (29.0 M)

WORKING HEIGHT: 100.0 FT (30.5 M)

HORIZONTAL REACH: 61.9 FT (18.9 M)

BOTTOM OF PLATFORM TO GROUND: -3.14 IN. (-8.0 CM)

UPPER BOOM EXTENSION: 251.7 IN. (639.3 CM)

LOWER BOOM ARTICULATION: 0 TO 88° UPPER BOOM TRAVEL: 75° TO -25°

LOWER BOOM INSULATION GAP: 24 IN. (61.0 CM) UPPER BOOM INSULATION GAP: 52 IN. (132.1 CM)

## **STANDARD EQUIPMENT:**

END-MOUNT 24" X 48" X 42" TWO-PERSON PLATFORM PLATFORM CAPACITY OF UP TO 700 LB (317.5 KG)

4-FUNCTION SINGLE STICK

SAFETY HARNESS WITH ATTACHED LANYARD

PLATFORM ROTATOR PROVIDES 180 DEGREES OF ROTATION

CONTINUOUS UNRESTRICTED WORM GEAR ROTATION

CATEGORY "C" RATING PER ANSI A92.2

RECTANGULAR, BI-AXIAL EPOXY RESIN, FILAMENT WOUND FIBERGLASS BOOMS

INDIVIDUAL LEVER LOWER CONTROLS

TWO SPEED MANUAL THROTTLE CONTROL

HYDRAULIC PLATFORM LEVELING SYSTEM

STEEL MAIN BOOM

FIBERGLASS SECOND SECTION BOOM

FIBERGLASS LOWER BOOM INSERT

FULL PRESSURE, OPEN-CENTER HYDRAULIC SYSTEM

DUAL HYDRAULIC TIOOLS WITH FLOW CONTROL

ENGINE STOP / START

35 GALLON HYDRAULIC OIL RESERVOIR W/ SIGHT & TEMP GAUGE (TL80)

50 GALLON HYDRAULIC OIL RESERVOIR W/ SIGHT & TEMP GAUGE (TL100 & TL80/112)

PADDED LOWER BOOM REST

**OUTRIGGER INTERLOCK** 







<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com